
















Project ventilation units				
Product	Description	Article number	Gross price €	Discount group
ComfoAir Standard				
	ComfoAir Standard 300 HRV comfort ventilation unit 300 m ³ /h (100 Pa) airflow volume, cross-counterflow heat exchanger with automatic summer bypass 100 %, for wall mounting, incl. wall plate, with & without pre-heater , different operation options available Dimensions: 702 x 845 x 572 mm (W x H x D)			
	ComfoAir Standard 300 L , left supply air connector	471 239 600	1.749,00	C
	ComfoAir Standard 300 R , right supply air connector	471 239 601	1.749,00	C
	ComfoAir Standard 300 VL , pre-heater & left supply air connector	471 239 602	1.899,00	C
	ComfoAir Standard 300 VR , pre-heater & right supply air connector	471 239 603	1.899,00	C
	ComfoAir Standard 375 HRV comfort ventilation unit 375 m ³ /h (100 Pa) airflow volume, cross-counterflow heat exchanger with automatic summer bypass 100 %, for wall mounting, incl. wall plate, with & without pre-heater, different operation options available Dimensions: 702 x 845 x 572 mm (W x H x D)			
	ComfoAir Standard 375 L , left supply air connector	471 239 608	1.849,00	C
	ComfoAir Standard 375 R , right supply air connector	471 239 609	1.849,00	C
	ComfoAir Standard 375 VL , pre-heater & left supply air connector	471 239 610	1.990,00	C
	ComfoAir Standard 375 VR , pre-heater & right supply air connector	471 239 611	1.990,00	C
	ComfoAir Standard 375 ERV comfort ventilation unit 375 m ³ /h (100 Pa) airflow volume, cross-counterflow enthalpy exchanger with automatic summer bypass 100 %, for wall mounting, incl. wall plate, with & without pre-heater , different operation options available Dimensions: 702 x 845 x 572 mm (W x H x D)			
	ComfoAir Standard 375 L ERV , left supply air connector	471 239 616	2.390,00	C
	ComfoAir Standard 375 R ERV , right supply air connector	471 239 617	2.390,00	C
	ComfoAir Standard 375 VL ERV , pre-heater & left supply air connector	471 239 618	2.549,00	C
	ComfoAir Standard 375 VR ERV , pre-heater & right supply air connector	471 239 619	2.549,00	C
	ComfoSense 55 control panel for ComfoAir 160, 180, 200, 350 and 550 suitable for installation into Jung, Gira and Busch-Jaeger switch ranges. Including 2 covers in RAL 9016 and 2 covers in RAL 9001 <i>CU-CFS55-9001/9016</i>	655 010 200	247,80	C
			Price valid until 31. March 2021	
	ComfoSense 67 control panel for ComfoAir 160, 180, 200, 350 and 550 Including cover frame, cover and surface-mounted housing in RAL 9016 <i>CU-CFS67-HSG-9016</i>	655 010 215	254,30	C
			Price valid until 31. March 2021	
	Remote-controlled control panel as an additional handset for the ComfoSense control panel <i>CU-RF-Z1</i>	655 000 755	108,80	C
			Price valid until 31. March 2021	
	ComfoSense connection cable for direct connection of the ComfoSense with built-in time control on the main PCB, lenght 250 mm <i>CON-CAB-CFS-ELT-PCK</i>	400 300 207	26,00	C

* Energy efficiency classes in accordance with EU regulation no. 1254/2014.

Energy efficiency classes for ComfoAir Standard are valid in connection with a three-stage switch or ComfoSense control panel.

** Energy efficiency classes for ComfoAir Standard are valid in connection with a CO₂ sensor.

Project ventilation units				
Product	Description	Article number	Gross price €	Discount group
ComfoAir Standard				
	Three-stage switch, in-wall, with 0 position for ComfoD 350, 200, 180, 160 & ComfoAir Standard 300/ 375	990 210 154	71,30	C
			Price valid until 31. March 2021	
	Three-stage switch, in-wall, without 0 position for ComfoD 350, 200, 180, 160 & ComfoAir Standard 300/ 375	659 000 120	60,80	C
			Price valid until 31. March 2021	
	Three-stage switch, in-wall, without 0 position, with fault indication for ComfoD 350, 200, 180, 160 & ComfoAir Standard 300/ 375	659 000 300	92,40	C
			Price valid until 31. March 2021	
	Surface-mounted housing for three-stage switch for ComfoD 350, 200, 180, 160 & ComfoAir Standard 300/ 375 suitable for 990 201 154	990 210 155	27,50	C
			Price valid until 31. March 2021	
	Surface-mounted housing for three-stage switch for ComfoD 350, 200, 180, 160 & ComfoAir Standard 300/ 375 suitable for 659 000 120 and 659 000 300	659 000 200	14,80	C
			Price valid until 31. March 2021	
	5-wire cable for operation of the ComfoAir Standard ventilation unit with a 3-stage switch, length 2500 mm	400 300 208	21,00	C
	CO₂-Sensor V55 , 55 mm for In-wall installation, suitable with most cover frames (not included) <i>SNS-CO2-V55</i>	655 000 845	330,00	C
			Price valid until 31. March 2021	
	CO₂-Sensor V67 , 67 mm for In-wall installation, cover frame in scope of delivery <i>CO2-SENSOR-0-10V-67</i>	655 000 850	330,00	C
			Price valid until 31. March 2021	
	CO₂-Sensor V67 , 67 mm for On-wall installation, on-wall socket and cover frame in scope of delivery <i>CO2-SENSOR-0-10V-67-ON-WALL</i>	655 000 855	345,00	C
			Price valid until 31. March 2021	
	LUXE PCB upgrade set add-on set for connection on the existing PCB of the ComfoAir Standard ventilation unit for connection of Zehnder CO ₂ sensors	471 230 005	413,20	B
			Price valid until 31. March 2021	
	ComfoAir Standard mounting base	642 300 135	150,10	C
			Price valid until 31. March 2021	
	Dry siphon 5 / 4" for ComfoAir 350 / 550 and ComfoFond-L Eco	990 201 330	49,40	C
			Price valid until 31. March 2021	
	Zehnder Pre-heater kit	471 230 000	365,70	C
			Price valid until 31. March 2021	
	Filter set for ComfoD 350, ISO Coarse ≥ 60 % (G4) 2 pieces <i>FIL-PFR-L500-W16.5-H197-SEL-CRS-2pc</i>	400 100 085	43,10	B
			Price valid until 31. March 2021	
	Filter set for ComfoD 350, ISO Coarse ≥ 60 % / ISO ePM1 ≥ 50 % (G4 / F7) 2 pieces <i>FIL-PFR-L500-W16.5-H197-SEL-CRS/ePM1</i>	400 100 084	45,70	B
			Price valid until 31. March 2021	

* Energy efficiency classes in accordance with EU regulation no. 1254/2014.
Energy efficiency classes for ComfoAir Standard are valid in connection with a three-stage switch or ComfoSense control panel.